

Part number list

WG12232L-□□□-□□#

Pin Assignment

Pin No.	Symbol	Description
1	V _{SS}	Ground
2	V _{DD}	Power supply for logic
3	V _O	Contrast Adjustment
4	RS	Data/ Instruction select signal
5	V _{out}	Positive Voltage output
6	NC	No connection
7	NC	No connection
8	E	Enable signal
9	R/W	Read/Write select signal
10	DB0	Data bus line
11	DB1	Data bus line
12	DB2	Data bus line
13	DB3	Data bus line
14	DB4	Data bus line
15	DB5	Data bus line
16	DB6	Data bus line
17	DB7	Data bus line
18	/RES	Controller reset signal, Active Low
19	A	Power supply for B/L +
20	K	Power supply for B/L -

Feature

1. Built-in controller ST7920
2. Built-in oscillation
3. +5V single power supply
4. 6800/SPI interface
5. Built-in Chinese font
6. (Option) +3V power supply with negative voltage




Mechanical Data

Item	Standard Value	Unit
Module Dimension	84.0 x 44.0	mm
Active Area	53.64 x 15.64	mm
Dot Pitch	0.44 x 0.49	mm
Dot Size	0.40 x 0.45	mm

Electrical Characteristics

Item	Symbol	Standard Value	Unit
		typ.	
Input Voltage	VDD	5.0	V

Mechanical Drawing



DOT SIZE
SCALE 10/1