

### Part number list

WG24064E-□□□-□□#

### Feature

1. Built-in controller RA6963 or equivalent
2. Built-in oscillation
3. +3V / +5V single power supply
4. 8080 interface
5. (Option) Built-in Negative voltage

### Pin Assignment

| Pin   | Symbol | Function                            |
|-------|--------|-------------------------------------|
| 1     | FG     | Frame ground                        |
| 2     | Vss    | Power supply (GND)                  |
| 3     | Vdd    | Power supply (+5V)                  |
| 4     | Vo     | Contrast Adjustment                 |
| 5     | /WR    | Data write                          |
| 6     | /RD    | Data read                           |
| 7     | /CE    | Chip enable                         |
| 8     | C/D    | Command/data                        |
| 9     | Vee    | Negative Voltage output             |
| 10    | /RST   | Reset signal                        |
| 11~18 | DB0~7  | Data bus line                       |
| 19    | FS     | Font select(H:6x8 L:8x8)            |
| 20    | NC/LED | No connection / Power supply (B/L-) |

### Mechanical Data

| Item             | Standard Value | Unit |
|------------------|----------------|------|
| Module Dimension | 180.0 x 60.0   | mm   |
| Active Area      | 127.17 x 33.89 | mm   |
| Dot Pitch        | 0.53 x 0.53    | mm   |
| Dot Size         | 0.50 x 0.50    | mm   |

### Electrical Characteristics

| Item          | Symbol | Standard Value | Unit |
|---------------|--------|----------------|------|
|               |        | typ.           |      |
| Input Voltage | VDD    | 3.0 / 5.0      | V    |

### Mechanical Drawing

