

Part number list

VGM128032B0□□□

Feature

- 1.Diagonal 0.88 inch
- 2.Built-in driver SSD1306BZ
- 3.Power supply : +2.8V & +12.5V
- 4.Built-in voltage booster
- 5.Interface: I2C
- 6.Temperature operating range: -40 ~70°C
- 7.Available color : White

Pin Assignment

Pin No.	Symbol	Description
1	C2P	Connect charge pump capacitor
2	C2N	Connect charge pump capacitor
3	C1P	Connect charge pump capacitor
4	C1N	Connect charge pump capacitor
5	VBAT	Power supply for booster
6	VSS	Ground
7	VDD	Power supply for logic
8	RES	Reset signal
9	SA0	Slave address select signal
10	SCL	Serial clock
11	SDA	Serial data
12	VCOMH	COM signal deselected voltage
13	VCC	OLED driving voltage input

Mechanical Data

Item	Standard Value	Unit
Panel Dimension	25.5 x 10.6	mm
Active Area	21.74 x 4.94	mm
Dot Pitch	0.17 x 0.155	mm
Dot Size	0.15 x 0.135	mm

Electrical Characteristics

Item	Symbol	Standard Value	Unit
		typ.	
Logic Voltage	VDD	2.8	V
OLED driving Voltage	VCC	12.5	V

Mechanical Drawing